



ZL18WFLRDRGBETL-24VDMX  
ZL24WFLRDRGBETL-24VDMX  
ZL36WFLRDRGBETL-DMX

## LED Flood Light RGB DMX512 ETL - Control

The LED Flood Light RGB DMX512 ETL - Control is designed to deliver a bright and accurate beam projection. Its die-casting aluminum body, tempered glass and durable IP66-rating ensures that the fixture works in any outdoor applications while being practically maintenance-free, which makes it a sustainable and long-lasting choice for both outdoor as well as indoor events and installations.

### Features and Benefits

- ETL Certificate
- 3 Year Warranty
- Different sizes and shapes
- Die-cast aluminum
- Tempered glass + optical lens



ZL60WFLSQRGBETL-DMX



### Applications

- Architecture lighting
- Entertainment lighting
- Building facade
- Tower and bridge



ZL100WFLSQRGBETL-DMX  
ZL150WFLSQRGBETL-DMX



### Technical Parameters

Product Code	Watts	Lumens	Voltage	Dimensions	Life Time	Control Driver	IP	Beam Angle	Warranty	Certificates
ZL18WFLRDRGBETL-24VDMX	18W	990lm	DC24 V	15"x7.7"	50,000 hrs	DMX512	IP66	45° *	3 years	ETL
ZL24WFLRDRGBETL-24VDMX	24W	1320lm	DC24 V	19"x9.9"	50,000 hrs	DMX512	IP66	45° *	3 years	ETL
ZL36WFLRDRGBETL-DMX	36W	1980lm	100-277 V	20.5"x10.1"	50,000 hrs	DMX512	IP66	45° *	3 years	ETL
ZL60WFLSQRGBETL-DMX	60W	3300lm	100-277 V	30.5"x23.5"x13"	50,000 hrs	DMX512	IP66	45° *	3 years	ETL
• ZL100WFLSQRGBETL-DMX	100W	5500lm	100-277 V	38"x19.5"x15.5"	50,000 hrs	DMX512	IP66	60° **	3 years	ETL
• ZL150WFLSQRGBETL-DMX	150W	8250lm	100-277 V	38"x19.5"x15.5"	50,000 hrs	DMX512	IP66	60° **	3 years	ETL

- NOTE • : Special product available upon request
- NOTE \* : Different beam angle available upon request (10°/15°/25°/30°/60°/90°)
- NOTE \*\* : Different beam angle available upon request (12°/24°/36°/90°)

For installation and safety notes visit: [www.zolulighting.com](http://www.zolulighting.com)

